

Pack of 10 twist drills DIN 338 type N HSS milled-ground with self-centering (Ø 9 mm)



Item: 214090
EAN-13: 4007140021854
URL: at.com.es/p/1017983
Brand: Ruko




image not found or type unknown

img src="https://imagenes.aghasaturis.com/rfc/ruko_angulo 118 copy.jpg" alt="" style="border:0px;">

- High performance drill bit, suitable for all types of drilling in common materials.
- High concentricity and rotational precision.
- Rectification in the form of a conical point with split point according to DIN 1412 C.
- Cutting angle: 118. Spiral angle: 20-30°.
- Ø-tolerance: h8.
- Glossy surface.
- Cut to the right.

Applications: for alloyed and unalloyed steel and cast steel (up to a strength of ca. 900 N/mm²), gray cast iron, malleable cast iron, nodular cast iron, pressure casting, sintered iron, nickel silver, graphite cast iron, aluminum alloys, bronze and brass.

Features

Ø (mm)	9
Overall length (mm)	125
Cutting length (mm)	81

Dimensiones

Item weight (kg)	0,04
Item length (cm)	12,50
Item width (cm)	0,90
Item height (cm)	0,90

Rate

Price unit	envase
Minimum quantity	1
Purchase condition	Multiples of 1

Packaging data

Content quantity	10,00
Content unit	Pieza
Packaged product: weight (kg)	0,40
Packaged product: length (cm)	13,00
Packaged product: width (cm)	4,00
Packaged product: height (cm)	4,00
Presentation	CHINA

Logistics data

Units contained in a package	10
Country of origin	China
Intrastat	8207506000
Available for dropshipping	si

Related products



MAXX flat blade
screwdriver

at.com.es/p/1017278



Work platform for 30
mm steps

at.com.es/p/1018569



Pack of twist drills DiN 338
type N HSS-G steamed
black

at.com.es/p/1018949



Pica Ink permanent deep
hole ink marker

at.com.es/p/1019227



Automatic marker with
interchangeable Pica Dry
graphite lead

at.com.es/p/1019575