



Round bearing M DIN EN 22568 HSS ground type B closed Thread M 24

Item: 237240

EAN-13: 4007140025241

URL: at.com.es/p/1018090

Brand: Ruko

For non-alloyed and low-alloyed steels up to a strength of 800 N/mm², non-ferrous metals.
The thread is tapped in 1 pass. 1 piece. Thread: metric DIN ISO 13. Tolerance: ISO - 6g. shiny surface.
Cut to the right. Individual plastic box with hanger.

Features

Measurements (mm)	M 24 x 3
Thread type	DIN ISO 13 (metric)
Ø thread (mm)	24
Step (mm)	3
Outer Ø (mm)	55
Thickness (mm)	22

Dimensiones

Item weight (kg)	0,26
Item length (cm)	6,50
Item width (cm)	6,50
Item height (cm)	2,00

Rate

Price unit	envase
Minimum quantity	1
Purchase condition	Multiples of 1

Packaging data

Content quantity	1,00
Content unit	Pieza
Packaged product: weight (kg)	0,26
Packaged product: length (cm)	6,50
Packaged product: width (cm)	6,50
Packaged product: height (cm)	2,00
Presentation	CHINA

Logistics data

Units contained in a package	1
Country of origin	China
Intrastat	8207403000
Available for dropshipping	si

Related products



PRO Hex T-Wrench
at.com.es/p/1017349



Magnetic hexagonal
socket in individual blister
at.com.es/p/1017474



Hand tap set M DIN 352
HSS ground
at.com.es/p/1018055



Machine tap M DIN 371
HSS-Co 5 ground type B
at.com.es/p/1018070



Adjustable tap wrench
DIN 1814
at.com.es/p/1018098